

FlameSpec™ IR3-H2-HD

Triple IR Flame Detector with HD Camera for Energy Transition

The FlameSpec™ IR3-H2-HD flame detector provides unrivaled response, high performance and reliable detection for a number of fires found in Energy Transition applications. The detector addresses slow growing fires as well as fast eruptions of fire using improved IR3 technology. The detector operates in all weathers and light conditions.

The detector provides high-definition (HD) video output of the monitored area with near IR filtered imaging of fire events and personnel at distances up to 100 ft (30 m). This allows the rescue team to be aware of the exact situation before entering the hazardous area.

Video and data of events are stored saved quickly to non-volatile memory for post incident investigation. The recordings start one minute before detection and continue for up to four minutes.

Key Benefits

- High immunity to false alarm, including arc welding.
- Detects, hydrogen, ammonia, methane & syngas flames using three infrared wavelengths, with clear separation.
- Each sensor has the same field of view to further improve false alarm immunity.
- HD, or composite, video output with automatic HD video recording of events.
- Ultra-fast detection mode detection within 40 milliseconds for fireballs or explosions.
- High speed (< 0.5 s) model [X5] available for the detection of fires in enclosed spaces.
- 5 selectable sensitivity levels.
- Data/Event logger – alarms, faults & videos as well as other relevant events are logged to non-volatile memory.
- Built-in-Test (BIT) – Automatic and manual self-test of window cleanliness and overall detector operation.
- Universal outputs, 3 and 4 wire, 4-20 mA sink / source, Fire, Auxiliary and Fault Relays. RS485 port using Modbus RTU.
- HART® 7 for configuration & maintenance - option available.
- Heated window to avoid condensation and icing.
- Stainless steel tilt mount with horizontal and vertical adjustment.
- Marine approval - DNV type approval.
- Functional safety - SIL 2 capable - option available.



FlameSpec™ IR3-H2-HD offers the fastest detection of flames and explosions, providing extra time that can be used to reduce damage to plant & property and evacuation of people.

FlameSpec™ IR3-H2-HD

Model: FLS-IR3-H2-HD

Triple IR Flame Detector with HD Camera for Energy Transition

Response Characteristics (Standard Model XO, X1 & X2)

Fuel	Size	Sensitivity	Distance ft (m)	Avrg Resp.Time (s)
Hydrogen	32-in Plume	Extreme	98 (30)	1.5
Hydrogen	32-in Plume	Medium	66 (20)	1.5
Hydrogen	32-in Plume	Low	33 (10)	1.4
Hydrogen	32-in Plume	Very Low	16 (5)	1.5
Methanol	1 x 1 ft	Extreme	59 (18)	4.2
Methanol	1 x 1 ft	Medium	30 (9)	2.9
Methanol	1 x 1 ft	Very Low	10 (3)	4.9
Methane	32-in Plume	Extreme	66 (20)	1.7
Methane	32-in Plume	Medium	52 (16)	1.2
Methane	32-in Plume	Low	26 (8)	1.4
Methane	32-in Plume	Very Low	13 (4)	0.9
Syngas (30%CH ₄ :70%H ₂)	32-in Plume	Extreme	82 (25)	3.0
Syngas (30%CH ₄ :70%H ₂)	32-in Plume	Medium	55 (17)	3.0
Syngas (30%CH ₄ :70%H ₂)	32-in Plume	Low	26 (8)	0.8
Syngas (30%CH ₄ :70%H ₂)	32-in Plume	Very Low	13 (4)	2.1

Response Characteristics (Fast Model X5)

Fuel	Size	Sensitivity	Distance ft (m)	Avrg Resp.Time (s)
Hydrogen	32-in Plume	Medium	59 (18)	0.1
Hydrogen	32-in Plume	Low	30 (9)	0.1
Hydrogen	32-in Plume	Very Low	16 (5)	0.2
Methanol	1 x 1 ft	Medium	26 (8)	0.3
Methanol	1 x 1 ft	Low	16 (5)	0.4
Methanol	1 x 1 ft	Very Low	8 (2.5)	0.3
Methane	32-in Plume	Medium	53 (16)	0.1
Methane	32-in Plume	Low	26 (8)	0.2
Methane	32-in Plume	Very Low	13 (4)	0.2
Syngas (30%CH ₄ :70%H ₂)	32-in Plume	Medium	50 (15)	0.4
Syngas (30%CH ₄ :70%H ₂)	32-in Plume	Low	23 (7)	0.2
Syngas (30%CH ₄ :70%H ₂)	32-in Plume	Very Low	13 (4)	0.1

FlameSpec™ IR3-H2-HD

Model: FLS-IR3-H2-HD

Triple IR Flame Detector with HD Camera for Energy Transition

Immunity to False Alarm

False Alarm Source	Modulated		Unmodulated	
	Distance ft (m)	Response	Distance ft (m)	Response
Sunlight, (direct or reflected)	No response			
Sunlight, (direct or reflected) with water droplets on sensors	No response			
Incandescent frosted glass light, 300W	2.0 (0.5)	No alarm	2.0 (0.5)	No alarm
Fluorescent, 70 W (3 x 23.3 W)	2.0 (0.5)	No alarm	2.0 (0.5)	No alarm
Electric arc	3.0 (1.0)	No alarm	3.0 (1.0)	No alarm
Arc welding	2.0 (0.5)	No alarm	2.0 (0.5)	No alarm
Radiation heater, 1850 W	2.0 (0.5)	No alarm	2.0 (0.5)	No alarm
Radiation heater, 1850 W with water droplets on the sensors	2.0 (0.5)	No alarm	2.0 (0.5)	No alarm
Quartz lamp (1000 W) shielded	2.0 (0.5)	No alarm	2.0 (0.5)	No alarm
Quartz lamp (500 W) non-shielded	2.0 (0.5)	No alarm	2.0 (0.5)	No alarm
Mercury vapor lamp 160 W x 3	2.0 (0.5)	No alarm	2.0 (0.5)	No alarm
Car exhausts	2.0 (0.5)	No alarm	2.0 (0.5)	No alarm
Projector led	2.0 (0.5)	No alarm	2.0 (0.5)	No alarm
Solenoid bell	2.0 (0.5)	No alarm	2.0 (0.5)	No alarm
Soldering iron	2.0 (0.5)	No alarm	2.0 (0.5)	No alarm
Electric drill	2.0 (0.5)	No alarm	2.0 (0.5)	No alarm

FlameSpec™ IR3-H2-HD

Model: FLS-IR3-H2-HD

Triple IR Flame Detector with HD Camera for Energy Transition

FIRE DETECTION	Detection Time and Distance	40 ms for fast fire burst or explosion 1.5 s for 32" (0.8 m) hydrogen fire at 0 – 66 ft (0 – 20 m) 4 s for 32" (0.8 m) hydrogen fire at 66 – 100 ft (20 – 30 m)
	Sensitivity Range	5 sensitivity ranges: Extreme, High, Medium, Low, Very Low
	Field of View (IR Detection)	90° Horizontal, 80° Vertical
	Time Delay	0 - 30 seconds
	Built in Test	Automatic and Manual
	VIDEO FUNCTIONALITY	HD Video
Video Recoding of Alarm Events		1 minute pre-event and up to 3 minutes post-event
System Integration Protocol		ONVIF (Open Network Video Interface Forum) Profile S
ELECTRICAL SPECIFICATIONS	Operating Voltage	24 VDC nominal (18 - 32 VDC)
	Current Consumption	Standby: 180 mA Maximum: 300 mA (including window heater)
	Electrical Entries	2x cable and conduit entries 3/4" NPT(F) or M25 x 1.5
	Wiring	14 - 17 AWG (2.5 – 1.0 mm ²)
OUTPUTS	Relays	SPST volt-free contacts rated 2A at 30 VDC 3 relays: Alarm & Auxiliary – normally open; Fault – normally closed
	0-20mA (Stepped) Current Output	3 wire and 4 wire configurations (sink and source) HART® rev 7.0 (option available)
	Indication	Tri-color LED (Green, Yellow, Red)
	Modbus	RTU compatible on RS-485
	Digital (for Video)	IP network IEEE 802.3 100Base-T
	Composite Video	NTSC or PAL
MECHANICAL SPECIFICATIONS	Size	7.87 x 5.12 x 5.12" (200 x 130 x 130 mm)
	Weight	Detector (Stainless Steel 316): 9.8 lbs. (4.4 kg) Tilt mount (Stainless Steel 316): 5.4 lbs. (2.4 kg)
ENVIRONMENTAL SPECIFICATIONS	Temperature Range	Operating: -67°F to +185°F (-55°C to +85°C) Storage: -67°F to +185°F (-55°C to +85°C)
	Humidity	Up to 99% (RH), non-condensing
	Ingress Protection	IP66 & 68; NEMA 4X & 6P
APPROVALS	ATEX	ATEX: II 2 G D Ex db IIC T6 Gb or Ex db eb IIC T6 Gb and Ex tb IIIC T85°C Db -55°C<Ta<60°C Ex db IIC T5 Gb or Ex db eb IIC T5 Gb and Ex tb IIIC T95°C Db -55°C<Ta<75°C Ex db IIC T4 Gb or Ex db eb IIC T4 Gb and Ex tb IIIC T105°C Db -55°C<Ta<85°C
	IECEX, INMETRO & PESO	Ex db IIC T6 Gb or Ex db eb IIC T6 Gb and Ex tb IIIC T85°C Db -50°C<Ta<60°C Ex db IIC T5 Gb or Ex db eb IIC T5 Gb and Ex tb IIIC T95°C Db -50°C<Ta<75°C Ex db IIC T4 Gb or Ex db eb IIC T4 Gb and Ex tb IIIC T105°C Db -50°C<Ta<85°C
	FMus & FMc	Class I, Div. 1, Groups B, C & D; T4 -50°C≤Ta≤85°C or T5 -50°C≤Ta≤75°C or T6 -50°C≤Ta≤60°C Class II/III, Div. 1, Groups E, F, G; T4 -50°C≤Ta≤85°C or T5 -50°C≤Ta≤75°C or T6 -50°C≤Ta≤60°C Class I, Zone 1, AEx/Ex db IIC T4 Gb or Class I, Zone 1, AEx/Ex db eb IIC T4 Gb -50°C≤Ta≤85°C Class I, Zone 1, AEx/Ex db IIC T5 Gb or Class I, Zone 1, AEx/Ex db eb IIC T5 Gb -50°C≤Ta≤75°C Class I, Zone 1, AEx/Ex db IIC T6 Gb or Class I, Zone 1, AEx/Ex db eb IIC T6 Gb -50°C≤Ta≤60°C Zone 21, AEx/Ex tb IIIC T105°C Db -50°C≤Ta≤85°C or Zone 21, AEx/Ex tb IIIC T95°C Db -50°C≤Ta≤75°C or Zone 21, AEx/Ex tb IIIC T80°C Db -50°C≤Ta≤60°C
	Performance	ANSI FM 3260
	Functional Safety	Certified SIL2 capable, per IEC 61508:2010 High & Low demand (option available)
	Marine	DNV Type Approval
	ACCESSORIES	Tilt mount, model FLS-TMO-S02
	Weather cover, model FLS-WCO-S02	Flame simulator, model FLS-FSIM-IR3-H2-KIT
	2" & 3" pole mount adapter, model FLS-PMA-S23	Airshield, model FLS-ASD-S02
	Duct mount with window, model FLS-DMW-S02	Duct mount for airshield, model FLS-DMX-S02
WARRANTY	5 years	